



U.S. Department of Labor

Occupational Safety and Health Administration
(Non-Mandatory Form)

Material Safety Data Sheet

May be used to comply with
OSHA's Hazard Communication Standard
29 CFR 1910.1200. Standard must be
consulted for specific requirements.

IDENTITY (*As Used on Label and List*)
ARDEX EP 2000 – HARDENER (PART A)

Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.

Section I

Manufacturer's Name
ARDEX ENGINEERED CEMENTS

Emergency Telephone Number
CHEM-TEL (800) 255-3924

Address (*Number, Street, City, State and Zip Code*)

Telephone Number for Information
(724) 203-5000

400 Ardex Park Drive
Aliquippa, PA 15001
U.S.A.

Date Prepared
August 2, 2001

Signature of Preparer (*Optional*)

Section II – Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity: Common Name(s))	OSHA PEL Recommended	OSHA PEL % (<i>optional</i>)	Other Limits ACGIH TLV
MIXTURE OF THE SUBSTANCES LISTED BELOW WITH HARMLESS ADDITIONS.			
DANGEROUS COMPONENTS:			
2855-13-2; 3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE; 20-50%			
1477-55-0; M-PHENYLENEBIS (METHYLAMINE); 10-20%			
100-51-6; BENZYL ALCOHOL; 10-20%			
694-83-7; CYCLOHEX-1,2-YLENEDIAMONE; 2.5-10%			
25620-58-0; TRIMETHYLHEXANE-1, 6-DIAMINE; <=2.5%			
25154-52-3; NONYLPHENOL; <=2.5%			

Section III – Physical/Chemical Characteristics

Boiling Point	205°C	Specific Gravity (H ₂ O = 1)	
Vapor Pressure (mm Hg)	0.1 hPa at 20°C	Melting Point	Not determined
Vapor Density (AIR = 1)	Ca 1 g/cm ³ at 20°C	Evaporation Rate (Butyl Acetate = 1)	
Solubility in Water	Emulsifiable		
Appearance and Odor	FLUID – YELLOW-BROWN – AMINE-LIKE		

Section IV – Fire and Explosion Hazard Data

Flash Point (Method Used) 101°C	Flammable Limits PRODUCT IS NOT SELF-IGNITING	LEL 1.3%	UEL 13.0%
Extinguishing Media USE FIRE-FIGHTING MEASURES THAT SUIT THE ENVIRONMENT.			
Special Fire Fighting Procedures NO SPECIAL MEASURES REQUIRED FOR PROTECTIVE EQUIPMENT.			
Unusual Fire and Explosion Hazards NO SPECIAL MEASURES REQUIRED. PRODUCT IS NOT EXPLOSIVE.			

ARDEX EP 2000, HARDENER (PART A) - Page 2

Section V – Reactivity Data

Stability	Unstable	<input type="checkbox"/>	Conditions to Avoid
	Stable	<input checked="" type="checkbox"/>	NONE

Incompatibility (*Materials to Avoid*)

NO DANGEROUS REACTIONS KNOWN.

Hazardous Decomposition or Byproducts

NO DECOMPOSITION IF USED ACCORDING TO SPECIFICATIONS. NO DANGEROUS DECOMPOSITION PRODUCTS KNOWN.

Hazardous Polymerization	May Occur	<input type="checkbox"/>	Conditions to Avoid
	Will Not Occur	<input checked="" type="checkbox"/>	NONE

Section VI – Health Hazard Data

Route(s) of Entry	Inhalation? YES	Skin? YES	Ingestion? YES
-------------------	--------------------	--------------	-------------------

Health Hazards (*Acute and Chronic*)

HARMFUL IN CONTACT WITH SKIN AND IF SWALLOWED. CAUSES BURNS. MAY CAUSE SENSITIZATION BY SKIN CONTACT. KEEP AWAY FROM FOODSTUFFS, BEVERAGES AND FOOD. WASH HANDS DURING BREAKS AND AT THE END OF THE WORK. AVOID CONTACT WITH THE EYES AND SKIN.

Carcinogenicity:	NTP? N/A	IARC Monographs? N/A	OSHA Regulated? N/A
------------------	-------------	-------------------------	------------------------

Signs and Symptoms of Exposure

HARMFUL IN CONTACT WITH SKIN AND IF SWALLOWED. CAUSES BURNS. MAY CAUSE SENSITIZATION BY SKIN CONTACT. WHEN USING DO NOT EAT OR DRINK. IN CASE OF CONTACT WITH EYES, RINSE IMMEDIATELY WITH PLENTY OF WATER AND SEEK MEDICAL ADVICE. AFTER CONTACT WITH SKIN, WASH IMMEDIATELY WITH PLENTY OF WATER. WEAR SUITABLE PROTECTIVE CLOTHING, GLOVES AND EYE/FACE PROTECTION. IN CASE OF ACCIDENT OR IF YOU FEEL UNWELL, SEEK MEDICAL ADVICE IMMEDIATELY. CAUSTIC EFFECT ON SKIN AND MUCOUS MEMBRANES. STRONG CAUSTIC EFFECT ON THE EYE. SWALLOWING WILL LEAD TO A STRONG CAUSTIC EFFECT ON MOUTH AND THROAT AND TO THE DANGER OF PERFORATION OF ESOPHAGUS AND STOMACH.

Medical Conditions Generally Aggravated by Exposure

N/A

Emergency First Aid Procedures

INSTANTLY REMOVE ANY SOILED AND IMPREGNATED GARMENTS BY THE PRODUCT. SYMPTOMS OF POISONING MAY EVEN OCCUR AFTER SEVERAL HOURS; THEREFORE, MEDICAL OBSERVATION FOR AT LEAST 48 HOURS AFTER THE ACCIDENT. **AFTER INHALATION**, SUPPLY FRESH AIR AND CALL FOR DOCTOR FOR SAFETY REASONS. IN CASE OF UNCONSCIOUSNESS BRING PATIENT INTO STABLE SIDE POSITION FOR TRANSPORT. **AFTER SKIN CONTACT**, INSTANTLY WASH WITH WATER AND SOAP AND RINSE THOROUGHLY. **AFTER EYE CONTACT**, RINSE OPENED EYE FOR SEVERAL MINUTES UNDER RUNNING WATER. THEN CONSULT DOCTOR. **AFTER SWALLOWING**, INSTANTLY CALL FOR DOCTOR. DRINK COPIOUS AMOUNTS OF WATER AND PROVIDE FRESH AIR.

Section VII – Precautions for Safe Handling and Use

Steps to Be Taken in Case Material is Released or Spilled

WEAR PROTECTIVE EQUIPMENT. KEEP UNPROTECTED PERSONS AWAY. PREVENT MATERIAL FROM REACHING SEWAGE SYSTEM, HOLES AND CELLARS. ABSORB WITH LIQUID ABSORBENT MATERIAL (SAND, DIATOMITE, ABSORBENTS, UNIVERSAL BINDERS, SAWDUCT). USE NEUTRALIZING AGENT.

Waste Disposal Method

MUST NOT BE DISPOSED OF TOGETHER WITH HOUSEHOLD REFUSE. DO NOT ALLOW PRODUCT TO REACH SEWAGE SYSTEM. PRODUCT RESTS, DRIED: EAK-CODE 170701. PRODUCT REST, NOT DRIED: EAK CODE 200112. EMPTY CONTAMINATED PACKAGINGS THOROUGHLY. THEY CAN BE RECYCLED AFTER THOROUGH AND PROPER CLEANING.

Precautions to Be Taken in Handling and Storing

THE PRODUCT DOES NOT CONTAIN ANY RELEVANT QUANTITIES OF MATERIALS WITH CRITICAL VALUES THAT HAVE TO BE MONITORED AT THE WORKPLACE. HAZARDOUS FOR WATER. DO NOT ALLOW PRODUCT TO REACH GROUNDWATER, LAKES, AND WATER COURSES OR SEWAGE SYSTEM. MUST NOT REACH SEWAGE WATER OR DRAINAGE DITCH UNDILUTED OR UNNEUTRALIZED. DANGER TO DRINKING WATER IF EVEN SMALL QUANTITIES LEAK INTO SOIL. STORAGE IN ONE COMMON FACILITY IS NOT REQUIRED.

Other Precautions

ENSURE ADEQUATE VENTILATION.

Section VIII – Control Measures

Respiratory Protection (*Specify Type*)

NOT REQUIRED

Ventilation	Local Exhaust AS REQUIRED	Special N/A
	Mechanical (<i>General</i>) N/A	Other N/A

Protective Gloves YES	Eye Protection TIGHTLY SEALED SAFETY GLASSES
--------------------------	---

Other Protective Clothing or Equipment

WEAR SUITABLE PROTECTIVE CLOTHING, GLOVES, AND EYE/FACE PROTECTION.

Work/Hygienic Practices

WHEN USING DO NOT EAT OR DRINK. AFTER CONTACT WITH SKIN, WASH IMMEDIATELY WITH PLENTY OF WATER.



Material Safety Data Sheet

May be used to comply with OSHA's Hazard Communication Standard 29 CFR 1910.1200. Standard must be consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration
(Non-Mandatory Form)

IDENTITY (As Used on Label and List)
ARDEX EP 2000, RESIN (PART B)

Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.

Section I

Manufacturer's Name
ARDEX ENGINEERED CEMENTS

Address (Number, Street, City, State and Zip Code)

400 Ardex Park Drive
Aliquippa, PA 15001
U.S.A.

Emergency Telephone Number
CHEM-TEL (800) 255-3924

Telephone Number for Information
(724) 203-5000

Date Prepared
August 3, 2001

Signature of Preparer (Optional)

Section II – Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity: Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (optional)
CAS NO. DESIGNATION: 25068-38-6 BISPHENOL A-(EPICHLORHYDRIN); EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT <700); EC NUMBER: 603-074-00-8				

Section III – Physical/Chemical Characteristics

Boiling Point	Not determined	Specific Gravity (H ₂ O = 1)	
Vapor Pressure (mm Hg)		Melting Point	Not determined
Vapor Density (AIR = 1)	Not determined	Evaporation Rate (Butyl Acetate = 1)	

Solubility in Water

NOT MISCIBLE OR DIFFICULT TO MIX

Appearance and Odor

Viscous – Colorless - Characteristic

Section IV – Fire and Explosion Hazard Data

Flash Point (Method Used) N/A	Flammable Limits N/A	LEL N/A	UEL N/A
----------------------------------	-------------------------	------------	------------

Extinguishing Media

SUITABLE EXTINGUISHING AGENTS.

Special Fire Fighting Procedures

FIGHT LARGER FIRES WITH WATER JET OR ALCOHOL-RESISTANT FOAM. NO SPECIAL MEASURES REQUIRED FOR PROTECTIVE EQUIPMENT. NO SPECIAL MEASURES REQUIRED FOR PROTECTION AGAINST EXPLOSIONS AND FIRES.

Unusual Fire and Explosion Hazards

PRODUCT IS NOT EXPLOSIVE.

Section V – Reactivity Data

Stability	Unstable	<input type="checkbox"/>	Conditions to Avoid
	Stable	<input checked="" type="checkbox"/>	NONE

Incompatibility (Materials to Avoid)

NO DANGEROUS REACTIONS KNOWN.

Hazardous Decomposition or Byproducts

NO DECOMPOSITION IF USED ACCORDING TO SPECIFICATIONS. NO DANGEROUS DECOMPOSITION PRODUCTS KNOWN.

Hazardous Polymerization	May Occur	<input type="checkbox"/>	Conditions to Avoid
	Will Not Occur	<input checked="" type="checkbox"/>	NONE

Section VI – Health Hazard Data

Route(s) of Entry	Inhalation? YES	Skin? YES	Ingestion? YES
Health Hazards (<i>Acute and Chronic</i>) N/A			
Carcinogenicity:	NTP? N/A	IARC Monographs? N/A	OSHA Regulated? N/A
Signs and Symptoms of Exposure SENSITIZATION POSSIBLY BY SKIN CONTACT. CONTAINS EPOXY CONSTITUENTS. IRRITANT FOR SKIN AND MUCOUS MEMBRANES. EYE IRRITANT EFFECT.			
Medical Conditions Generally Aggravated by Exposure N/A			
Emergency First Aid Procedures AFTER INHALATION: SUPPLY FRESH AIR AND CALL FOR DOCTOR FOR SAFETY REASONS. IN CASE OF UNCONSCIOUSNESS, BRING PATIENT INTO STABLE SIDE POSITION FOR TRANSPORT. AFTER SKIN CONTACT: INSTANTLY WASH WITH WATER AND SOAP AND RINSE THOROUGHLY. AFTER EYE CONTACT: RINSE OPENED EYE FOR SEVERAL MINUTES UNDER RUNNING WATER. IF SYMPTOMS PERSIST, CONSULT DOCTOR. AFTER SWALLOWING, INSTANTLY CALL FOR DOCTOR.			

Section VII – Precautions for Safe Handling and Use

Steps to Be Taken in Case Material is Released or Spilled HAZARDOUS FOR WATER. PREVENT MATERIAL FROM REACHING SEWAGE SYSTEM, HOLES, AND CELLARS. DO NOT ALLOW PRODUCT TO REACH GROUNDWATER, LAKES, AND WATER COURSES. DANGER TO DRINKING WATER IF EVEN SMALL QUANTITIES LEAK INTO SOIL. ABSORB WITH LIQUID ABSORBENT MATERIAL (SAND, DIATOMITE, ABSORBENTS, UNIVERSAL BINDERS, SAWDUST). PERSONAL SAFETY PRECAUTIONS NOT REQUIRED.	
Waste Disposal Method MUST NOT BE DISPOSED OF TOGETHER WITH HOUSEHOLD REFUSE. DO NOT ALLOW PRODUCT TO REACH SEWAGE SYSTEM. UNCLEANED PACKAGINGS – RECOMMENDATION: EMPTY CONTAMINATED PACKAGINGS THOROUGHLY. THEY CAN BE RECYCLED AFTER THOROUGH AND PROPER CLEANING.	
Precautions to Be Taken in Handling and Storing ENSURE GOOD VENTILATION/EXHAUSTION AT THE WORKPLACE. COMMON STORAGE FACILITY NOT REQUIRED.	
Other Precautions PROTECT FROM FROST. KEEP CONTAINER TIGHTLY SEALED.	

Section VIII – Control Measures

Respiratory Protection (<i>Specify Type</i>) NOT REQUIRED	
Ventilation	Local Exhaust INSURE GOOD VENTILATION/EXHAUSTION
	Mechanical (<i>General</i>) N/A
	Special N/A
	Other N/A
Protective Gloves YES	Eye Protection TIGHTLY SEALED SAFETY GLASSES
Other Protective Clothing or Equipment N/A	
Work/Hygienic Practices AVOID CONTACT WITH THE EYES AND SKIN. WASH HANDS DURING BREAKS AND AT THE END OF WORK. INSTANTLY REMOVE ANY SOILED AND IMPREGNATED GARMETS. KEEP AWAY FROM FOODSTUFFS, BEVERAGES, AND FOOD.	