

Material Safety Data Sheet

24-Hour Emergency Telephone Number

1-800-424-9300 (Chemtree)



MSDS #: 91092

MSDS #: 91092
DATE OF PREPARATION: 6/15/2005
LAST REVISION DATE: 6/15/2005

HMIS Ratings:

HEALTH: 2
FLAMMABILITY: 2
REACTIVITY: 0
PROTECTION: G

SECTION I - PRODUCT IDENTIFICATION

PRODUCT NAME: WOODLINE® 350 POLYURETHANE (GLOSS)

PRODUCT DESCRIPTION: OIL MODIFIED URETHANE FINISH FOR WOOD FLOORS

SECTION II - HAZARDOUS INGREDIENTS

INGREDIENT	CAS #	% WEIGHT	Occupational Exposure Limits		VAPOR PRESSURE- mm Hg
			ACGIH-TLV	OSHA-PEL	
LINSEED OIL	8001-26-1	<10%	N/E	N/E	N/E
OCTAMETHYLCYCLOTETRAILOXANE	556-67-2	10-15%	NE	NE	0.12@25C
PETROLEUM DISTILLATES - LIGHT	64742-47-8	15-20%	N/E	500 PPM	2.00 @ 20C
STODDARD SOLVENT	8052-41-3	10-15%	100 PPM	500 PPM	2.00 @ 20C

SECTION III - PHYSICAL DATA

BOILING RANGE: 300F-330F (149-166C)

EVAPORATION RATE: Slower than n-Butyl Acetate

% VOLATILE - WT: 47

DENSITY: 7.87LBS/GAL (0.95KG/L)

VAPOR DENSITY: Heavier than air

SOLUBILITY IN WATER: Insoluble

PRODUCT CHARACTERISTICS: Amber, slightly thick liquid with solvent odor

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLAMMABILITY CLASSIFICATION: OSHA - Combustible Liquid Class II

FLASH POINT: 104F (43C) PMCC

% OF VOL. OF FLAMMABLE LIMITS (Upper): 11.00

(Lower): 1.00

EXTINGUISHING MEDIA: Carbon Dioxide, Dry Chemical, Foam, and/or Water Fog

UNUSUAL FIRE EXPLOSION HAZARDS:

Vapors are heavier than air and may travel along the ground or be moved by ventilation and ignited by heat, pilot lights, other flames and ignition sources at locations distant from material handling point. Extinguish all sources of flame or spark. Keep containers tightly closed when not in use. Closed containers may explode when exposed to extreme heat. DANGER: Rags, steel wool or waste contaminated with this product may spontaneously catch fire. Immediately after each use, place contaminated rags, steel wool or waste in a sealed, water-filled metal container.

SPECIAL FIREFIGHTING PROCEDURES:

See 2000 North American Emergency Response Guidebook - Guide 128. Wear self-contained breathing apparatus with full facepiece operated in pressure demand or other positive pressure mode. Irritating or toxic substances may be emitted upon thermal decomposition. Avoid breathing vapors.