

# MATERIAL SAFETY DATA SHEET

## STONE SPECIFIC GRANITE POLISH

<b>HMIS</b>	
HEALTH	1
FLAMMABILITY	2
REACTIVITY	0
PERSONAL PROTECTION	G

### 1. Product And Company Identification

<p><b>Supplier</b>                  CUSTOM BUILDING PRODUCTS                  10400 Pioneer Blvd., Unit #3                  Santa Fe Springs, CA 90670 UNITED STATES</p> <p><b>Company Contact:</b> GEORGE MARCINA  <b>Telephone Number:</b> (562) 968-2980 Ext 103  <b>FAX Number:</b> (562) 903-2697  <b>E-Mail:</b> georgem@cbpmail.net  <b>Web Site:</b> www.custombuildingproducts.com</p>	<p><b>Manufacturer</b>                  CUSTOM BUILDING PRODUCTS                  10400 Pioneer Blvd., Unit #3                  Santa Fe Springs, CA 90670 UNITED STATES</p> <p><b>Company Contact:</b> GEORGE MARCINA  <b>Telephone Number:</b> (562) 968-2980 Ext 103  <b>FAX Number:</b> (562) 903-2697  <b>E-Mail:</b> georgem@cbpmail.net  <b>Web Site:</b> www.custombuildingproducts.com</p>
---	---

<p><b>Supplier Emergency Contacts &amp; Phone Number</b>                  GEORGE MARCINA: (562) 968-2980</p>	<p><b>Manufacturer Emergency Contacts &amp; Phone Number</b>                  GEORGE MARCINA: (562) 968-2980</p>
--	--

**Issue Date:** 03/16/2006

**Product Name:** STONE SPECIFIC GRANITE POLISH  
**CAS Number:** Not Established  
**Chemical Formula:** MIXTURE  
**MSDS Number:** 569  
**Product Code:** RM9236

### 2. Composition/Information On Ingredients

Ingredient Name	CAS Number	Percent Of Total Weight
SILICONEI	110475-82-0	1 - 5
SILICONEII	99363--37-8	1 - 5
SILICONEIII	71750-80-6	1 - 5
MINERALSPIRITS	64742-96-7	20 - 25

### 3. Hazards Identification

**Primary Routes(s) Of Entry**  
 EYES, SKIN, INHALATION, INGESTION.

**Eye Hazards**  
 MAY CAUSE IRRITATION

**Skin Hazards**  
 MAY CAUSE IRRITATION.

**Ingestion Hazards**  
 MAY CASUE IRRITATION. SEEK MEDICAL HELP.

**Inhalation Hazards**  
 VAPORS MAY CAUSE IRRITATION TO NOSE, THROAT AND RESPIRATORY TRACT.

# MATERIAL SAFETY DATA SHEET

## STONE SPECIFIC GRANITE POLISH

### 3. Hazards Identification - Continued

#### Conditions Aggravated By Exposure

PRE- EXISTING EYE, SKIN AND RESPIRATORY CONDITIONS MAY BE AGGRAVATED.

### 4. First Aid Measures

#### Eye

WASH EYES WITH RUNNING COLD WATER FOR 15 MINUTES WHILE HOLDING EYELIDS OPEN. CONSULT PHYSICIAN

#### Skin

WASH OFF WITH WATER AND SOAP.

#### Ingestion

DO NOT INDUCE VOMITING. IF VOMITING OCCURS, KEEP HEAD BELOW HIPS. GET MEDICAL ATTENTION.

#### Inhalation

REMOVE VICTIM TO FRESH AIR AND PROVIDE OXYGEN IF BREATHING IS DIFFICULT.

### 5. Fire Fighting Measures

**Flash Point:** > 200 F °F

**Flash Point Method:** PMCC

**Lower Explosive Limit:** NA

**Upper Explosive Limit:** NA

#### Fire And Explosion Hazards

KEEP AWAY FROM OPEN FLAME AND OTHER SOURCES OF IGNITION.

#### Extinguishing Media

USE FOAM, DRY CHEMICAL OR CO2.

#### Fire Fighting Instructions

DO NOT ENTER CONFINED FIRE SPACE WITHOUT FULL BUNKER GEAR, INCLUDING A PRESSURE NIOSH APPROVED SELF-CONTAINED BREATHING APPARATUS, COOL FIRE EXPOSED CONTAINERS WITH WATER.

### 6. Accidental Release Measures

IN CASE MATERIAL IS RELEASED OR SPILLED, TAKE UP WITH AN ABSORBENT MATERIAL AND PLACE IN NON LEAKING CONTAINERS FOR PROPER DISPOSAL.

### 7. Handling And Storage

#### Handling And Storage Precautions

STORE IN AREA AWAY FROM HEAT, SPARKS AND FLAME.

#### Handling Precautions

KEEP CONTAINERS CLOSED. KEEP FROM FREEZING

#### Storage Precautions

STORE IN A COOL, VENTILATED PLACE, AWAY FROM SPARKS OR OPEN FLAME. AVOID FREEZING.

#### Work/Hygienic Practices

GOOD HOUSEKEEPING PRINCIPLES SHOULD BE PRACTICED AT ALL TIMES. EMPTY CONTAINERS MAY CONTAIN RESIDUE AND MAYBE HAZARDOUS.

### 8. Exposure Controls/Personal Protection

#### Eye/Face Protection

CHEMICAL SPLASH GOGLES

# MATERIAL SAFETY DATA SHEET

## STONE SPECIFIC GRANITE POLISH

### 8. Exposure Controls/Personal Protection - Continued

#### Skin Protection

CHEMICAL RESISTANT GLOVES

#### Respiratory Protection

GENERAL ROOM VENTILATION IS USUALLY ADEQUATE

#### Other/General Protection

OBSERVE GOOD HOUSEKEEPING PRACTICES.

#### Ingredient(s) - Exposure Limits

MINERAL SPIRITS

ACGIH TLV-TWA 100 ppm

OSHA PEL-TWA 500 ppm

OSHA VPEL - TWA 100 ppm

### 9. Physical And Chemical Properties

#### Appearance

WHITE OPAQUE LIQUID.

#### Odor

MILD PETROLEUM ODOR.

**Chemical Type:** Mixture

**Physical State:** Liquid

**Boiling Point:** 212 °F

**Specific Gravity:** < 1.0

**Percent Volatiles:** 75% by vol.

**Percent VOCs:** 185 g/l

**Solubility:** IN MINERAL SPIRITS

### 10. Stability And Reactivity

**Stability:** STABLE

**Hazardous Polymerization:** WILL NOT OCCUR.

#### Conditions To Avoid (Stability)

AVOID HEAT, FLAME AND CONTACT WITH STRONG OXIDIZING AGENTS.

#### Hazardous Decomposition Products

CO, CO<sub>2</sub> SiO<sub>2</sub> AND POSSIBLY OTHER ORGANIC COMPOUNDS MAY BE FORMED DURING COMBUSTION.

### 11. Toxicological Information

No Data Available...

### 12. Ecological Information

No Data Available...

### 13. Disposal Considerations

DISPOSE OF PRODUCT IN ACCORDANCE WITH LOCAL, STATE OR FEDERAL REGULATIONS.

#### RCRA Information

NOT CONSIDERED RCRA WASTE

### 14. Transport Information

No Data Available...

# MATERIAL SAFETY DATA SHEET

## STONE SPECIFIC GRANITE POLISH

### 15. Regulatory Information

#### Ingredient(s) - State Regulations

MINERAL SPIRITS

New Jersey - Workplace Hazard

Pennsylvania - Workplace Hazard

Massachusetts - Hazardous Substance

New York City - Hazardous Substance

### 16. Other Information

#### HMIS Rating

Health: 1

Fire: 2

Reactivity: 0

Personal Protection: G

#### Revision/Preparer Information

MSDS Preparer: GEORGE MARCINA

MSDS Preparer Phone Number: (323) 582-0846

This MSDS Supercedes A Previous MSDS Dated: 02/17/2006

#### Disclaimer

THE INFORMATION PRESENTED HERE IS BELIEVED TO BE ACCURATE BUT IS NOT WARRANTED TO BE, WHETHER ORIGINATING WITH THE COMPANY OR NOT. RECIPIENTS ARE ADVISED TO CONFIRM IN ADVANCE OF NEED, THAT THE INFORMATION IS CURRENT AND SUITABLE TO THEIR CIRCUMSTANCES.

CUSTOM BUILDING PRODUCTS

Printed Using MSDS Generator™ 2000