

MATERIAL SAFETY DATA SHEET

STONESPECIFIC STONE GLOSS POLISH

HMIS

HEALTH	1
FLAMMABILITY	2
REACTIVITY	0
PERSONAL PROTECTION	G

1. Product And Company Identification

Supplier

CUSTOM BUILDING PRODUCTS
10400 Pioneer Blvd., Unit #3
Santa Fe Springs, CA 90670 UNITED STATES

Company Contact: GEORGE MARCINA
Telephone Number: (562) 968-2980 Ext 103
FAX Number: (562) 903-2697
E-Mail: georgem@cbpmail.net
Web Site: www.custombuildingproducts.com

Manufacturer

CUSTOM BUILDING PRODUCTS
10400 Pioneer Blvd., Unit #3
Santa Fe Springs, CA 90670 UNITED STATES

Company Contact: GEORGE MARCINA
Telephone Number: (562) 968-2980 Ext 103
FAX Number: (562) 903-2697
E-Mail: georgem@cbpmail.net
Web Site: www.custombuildingproducts.com

Supplier Emergency Contacts & Phone Number

GEORGE MARCINA: (562) 968-2980

Manufacturer Emergency Contacts & Phone Number

GEORGE MARCINA: (562) 968-2980

Issue Date: 03/16/2006

Product Name: STONESPECIFIC STONE GLOSS POLISH
CAS Number: Not Established
MSDS Number: 30
Product Code: 3056

2. Composition/Information On Ingredients

Ingredient Name	CAS Number	Percent Of Total Weight
WAX	8002-74-2	1 - 5
DIETHYLENEGLYCOLMONOBUTYLETHER	112-34-5	1 - 5
SOLVENTNAPHTHA,PETROLEUM	64742-48-9	85 - 95

OSHA HAZARD. COMBUSTIBLE.

3. Hazards Identification

Primary Routes(s) Of Entry

EYES, SKIN AND NOSE.

Eye Hazards

May cause eye irritation..

Skin Hazards

MAY CAUSE IRRITATION. IF IN CONTACT FOR LONG PERIODS OF TIME, MAY RESULT IN DEFATTING AND DRYING OF THE SKIN.

Ingestion Hazards

MAY RESULT IN VOMITING. ASPIRATION OF VOMITUS INTO LUNGS MAY RESULT IN ASPIRATION PNEUMONITIS.

MATERIAL SAFETY DATA SHEET

STONESPECIFIC STONE GLOSS POLISH

3. Hazards Identification - Continued

Inhalation Hazards

VAPORS MAY CAUSE IRRITATION TO NOSE, THROAT AND RESPIRATORY TRACT.

Conditions Aggravated By Exposure

EYE, SKIN AND RESPIRATORY CONDITIONS MAY BE AGGRAVATED.

ACUTE: ASPIRATION PNEUMONITIS MAY BE EVIDENCED BY COUGHING, LABORED BREATHING AND CYANOSIS. IN SEVERE CASES, DEATH MAY OCCUR.

4. First Aid Measures

Eye

WASH EYES WITH RUNNING COLD WATER FOR 15 MINUTES WHILE HOLDING EYELIDS OPEN. CONSULT PHYSICIAN

Skin

WASH OFF WITH WATER AND SOAP.

Ingestion

DO NOT INDUCE VOMITING. IF VOMITING OCCURS, KEEP HEAD BELOW HIPS. GET MEDICAL ATTENTION.

Inhalation

REMOVE VICTIM TO FRESH AIR AND PROVIDE OXYGEN IF BREATHING IS DIFFICULT.

5. Fire Fighting Measures

Flash Point: 104 °F

Flash Point Method: TCC

Autoignition Point: 689 °F

Flammability Class: Combustible Liquid

Lower Explosive Limit: 0.7

Upper Explosive Limit: 5.6

Fire And Explosion Hazards

COMBUSTIBLE LIQUID

CONTAINERS EXPOSED TO INTENSE HEAT SHOULD BE COOLED WITH WATER TO PREVENT VAPOR PRESSURE BUILD-UP WHICH COULD RESULT IN EXPLOSION.

EMPTY CONTAINERS RETAIN PRODUCT RESIDUE AND MAY BE DANGEROUS.

MATERIAL CAN ACCUMULATE STATIC CHARGES WHICH CAN CAUSE INCENDIARY ELECTRICAL DISCHARGE.

Extinguishing Media

USE FOAM, DRY CHEMICAL OR CO2. DO NOT USE A DIRECT STREAM OF WATER. PRODUCT WILL FLOAT AND CAN BE RE-IGNITED ON SURFACE OF WATER.

Fire Fighting Instructions

COMBUSTIBLE. DO NOT ENTER CONFINED FIRE SPACE WITHOUT FULL BUNKER GEAR, INCLUDING A PRESSURE NIOSH APPROVED SELF-CONTAINED BREATHING APPARATUS, COOL FIRE EXPOSED CONTAINERS WITH WATER.

6. Accidental Release Measures

CAUTION: MATERIAL IS COMBUSTIBLE. IN CASE MATERIAL IS RELEASED OR SPILLED, TAKE UP WITH AN ABSORBENT MATERIAL AND PLACE IN NON LEAKING CONTAINERS FOR PROPER DISPOSAL. EMPTY CONTAINERS MAY CONTAIN RESIDUE - LIQUID AND VAPOR AND MAY BE DANGEROUS.

7. Handling And Storage

No Data Available...

MATERIAL SAFETY DATA SHEET

STONESPECIFIC STONE GLOSS POLISH

7. Handling And Storage - Continued

Handling And Storage Precautions

STORE IN AREA AWAY FROM HEAT, SPARKS AND FLAME.

Handling Precautions

KEEP CONTAINERS CLOSED. HANDLE WITH CARE. MATERIAL WILL ACCUMULATE STATIC CHARGES AND MAY CAUSE ELECTRICAL SPARK AND IGNITION.

Storage Precautions

STORE IN A COOL, VENTILATED PLACE, AWAY FROM SPARKS OR OPEN FLAME.

Work/Hygienic Practices

GOOD HOUSEKEEPING PRINCIPLES SHOULD BE PRACTICED AT ALL TIMES.
EMPTY CONTAINERS MAY CONTAIN RESIDUE AND MAYBE HAZARDOUS.

8. Exposure Controls/Personal Protection

Eye/Face Protection

Chemical splash goggles.

Skin Protection

Chemical-resistant gloves.

Respiratory Protection

General room ventilation is normally adequate.

Other/General Protection

Good housekeeping rules should be observed.

Ingredient(s) - Exposure Limits

DIETHYLENE GLYCOL MONOBUTYL ETHER

TWA - 35 ppm

SOLVENT NAPHTHA, PETROLEUM

OSHA/PEL = 100PPM

ACGIH/TLV = 100 PPM

TWA - 1200 mg.m3

NONE REQUIRED.

9. Physical And Chemical Properties

Appearance

LIGHT COLORED LIQUID.

Odor

HYDROCARBON ODOR.

Chemical Type: Mixture

Physical State: Liquid

Boiling Point: 320 - 350 °F

Specific Gravity: 0.8

Vapor Pressure: 1.73

Vapor Density: 5.3

Solubility: NEGLIGIBLE

Evaporation Rate: 0.2

10. Stability And Reactivity

Stability: STABLE

Hazardous Polymerization: WILL NOT OCCUR.

MATERIAL SAFETY DATA SHEET

STONESPECIFIC STONE GLOSS POLISH

10. Stability And Reactivity - Continued

Conditions To Avoid (Stability)

AVOID HEAT, FLAME AND CONTACT WITH STRONG OXIDIZING AGENTS.

Hazardous Decomposition Products

CARBON MONOXIDE AND UNIDENTIFIED ORGANIC COMPOUNDS MAY BE FORMED DURING COMBUSTION.

11. Toxicological Information

No Data Available...

12. Ecological Information

No Data Available...

13. Disposal Considerations

DISPOSE OF PRODUCT IN ACCORDANCE WITH LOCAL, STATE OR FEDERAL REGULATIONS.

14. Transport Information

Additional Shipping Paper Description

IN CONTAINERS OF 119 GAL OR LESS THIS PRODUCT IS NOT REGULATED BY DOT

15. Regulatory Information

SARA Hazard Classes

Fire Hazard

Ingredient(s) - U.S. Regulatory Information

DIETHYLENE GLYCOL MONOBUTYL ETHER

SARA Title III - Section 313 Form "R"/TRI Reportable Chemical

SARA - Acute Health Hazard

SARA - Chronic Health Hazard

SOLVENT NAPHTHA, PETROLEUM

OSHA Process Safety Management - 1910.119 App A Hazardous Chemical

SARA - Fire Hazard

Ingredient(s) - State Regulations

WAX

Pennsylvania - Workplace Hazard

Massachusetts - Hazardous Substance

DIETHYLENE GLYCOL MONOBUTYL ETHER

New Jersey - Workplace Hazard

New Jersey - Environmental Hazard

New York City - Hazardous Substance

16. Other Information

HMIS Rating

Health: 1

Fire: 2

Reactivity: 0

Personal Protection: G

Revision/Preparer Information

MSDS Preparer: GEORGE MARCINA

MSDS Preparer Phone Number: (323) 582-0846

MATERIAL SAFETY DATA SHEET

STONESPECIFIC STONE GLOSS POLISH

Disclaimer

THE INFORMATION PRESENTED HERE IS BELIEVED TO BE ACCURATE BUT IS NOT WARRANTED TO BE, WHETHER ORIGINATING WITH THE COMPANY OR NOT. RECIPIENTS ARE ADVISED TO CONFIRM IN ADVANCE OF NEED, THAT THE INFORMATION IS CURRENT AND SUITABLE TO THEIR CIRCUMSTANCES.

CUSTOM BUILDING PRODUCTS

Printed Using MSDS Generator™ 2000