

# MSDS Material Safety Data Sheet

Wilsonart International



MSDS Number: 01950  
Page 1 of 6

Wilsonart®/Lokweld® 700A Adhesive

Revision Date: 01/22/10  
Revision No: 4

## 1 PRODUCT AND COMPANY IDENTIFICATION

**Common Name:** Wilsonart®/Lokweld® 700A Adhesive

**Manufacturer:** WILSONART INTERNATIONAL, INC.  
P. O. BOX 6110 – 2400 WILSON PLACE  
TEMPLE, TX 76503  
**INFORMATION PHONE:** 800-433-3222 (USA)

**Trade Name:** WA/LW 700A Adhesive

**Material Uses:** Adhesive for laminate

**In Case of Emergency Contact CHEMTREC:** 800-424-9300 (USA)  
703-527-3887 (INTERNATIONAL)

## 2 HAZARDS IDENTIFICATION

**Route of Entry:** Skin, eyes, respiratory tract.

**Target Organs:** Lung, liver, kidney, central nervous system (CNS), and peripheral nervous system.

**Inhalation:** Breathing vapors may cause irritation to the respiratory tract and Central Nervous System (CNS) depression with headache, nausea, and dizziness. Intentional overexposure of concentrated vapors by direct inhalation is extremely hazardous.

**Skin Contact:** May cause frostbite. May cause skin irritation. May aggravate pre-existing skin conditions.

**Eye Contact:** Will cause eye irritation.


**Ingestion:** Not an expected route of entry. If ingested it may cause irritation to the gastro-intestinal tract.

DANGER!

EXTREMELY FLAMMABLE LIQUID AND VAPOR. VAPOR MAY CAUSE FLASH FIRE. HARMFUL IF INHALED OR SWALLOWED. MAY CAUSE RESPIRATORY TRACT, EYE AND SKIN IRRITATION. USE ONLY WITH ADEQUATE VENTILATION.

HMIS (United States):	
HEALTH	2*
FLAMMABILITY	4
REACTIVITY	0
PPE	C

NFPA (United States):



WHMIS (Canada): A, B1, D2B



\*See Section 11

## 3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	CAS#	% by Weight
Acetone	67-64-1	20 – 30
Dimethyl Ether	115-10-6	10 – 20
Propane	74-98-6	10 – 20

# MSDS *Material Safety Data Sheet*

Wilsonart International



MSDS Number: 01950  
Page 2 of 6

Wilsonart®/Lokweld® 700A Adhesive

Revision Date: 01/22/10  
Revision No: 4

Pentane	109-66-0	< 15
Light Hydrotreated Distillate	68410-97-9	1 – 10
Toluene	108-88-3	4 – 8
Cyclohexane	110-82-7	< 1.5
n-Hexane	110-54-3	< 0.3

## 4 FIRST AID MEASURES

**Inhalation:** Remove patient to fresh air. If patient is having difficulty breathing, seek immediate medical attention. If not breathing, clear airway and start mouth-to-mouth artificial respiration (or use bag-mask respirator). Seek immediate medical attention.

**Skin Contact:** Wash affected areas with soap and water. If irritation develops, seek medical attention.

**Eye Contact:** Flush eyes with water for 15 minutes. Remove contact lenses prior to water flush. Seek medical attention.

**Ingestion:** DO NOT induce vomiting. Seek immediate medical attention. DO NOT give anything by mouth to an unconscious person.

## 5 FIRE FIGHTING MEASURES

**Flash Point:** -156°F (-104°C) estimated

**Flash Point Method:** Open Cup

**Autoignition Temp.:** 473°F (245°C) (Cyclohexane)

**Burning Rate:** Not Available

**LEL:** 2.3% (Propane)

**UEL:** 9.5% (Propane)

**Flammability Classification:** Flammable Gas

**Firefighting Equipment:** Use self-contained breathing apparatus with a full-face piece and pressure demand or other positive-pressure mode.

**Risk of explosion due to mechanical impact:** Not Available.

**Risk of explosion due to static discharge:** Static discharge may serve as an ignition source for this product.

**Hazardous Products of Combustion:** Carbon Oxides (CO and CO<sub>2</sub>) and various Hydrocarbons.

**Special remarks:** Extremely flammable liquid and vapor. Vapor may cause flash fires. Vapors are heavier than air and can travel long distances to ignition sources. Aerosol containers can explode in a fire. In case of fire, use dry chemicals, CO<sub>2</sub>, or alcohol foam. Avoid water. Cool containing vessels with water jet to prevent pressure build-up, autoignition, or explosion. All electrical equipment in area must be rated for flammable liquids.

## 6 ACCIDENTAL RELEASE MEASURES

**Personal Precautions:** Wear appropriate PPE. Extremely flammable. Remove all sources of ignition. Make sure area is well ventilated. Spilled adhesive may be slippery.

**Environmental Precautions:** Keep out of sewers and drains.

**Clean-up methods:** Dike and contain spill. Absorb spilled product with vermiculite, dry sand, or earth. Place in a suitable non-leaking container and tightly seal for disposal.

## 7 HANDLING AND STORAGE

**Handling Precautions:** Wear appropriate PPE. Keep away from heat, sparks, and flames. If used indoors, make sure to provide adequate ventilation to prevent vapor build-up.

**Storage Requirements:** Store in a cool, (below 120°F or 49°C) dry, well-ventilated area. Ensure product is kept away from all sources of heat and sparks. Prohibit smoking in the storage area. Do not store with acids or oxidizers.

## 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

**Engineering Controls:** Provide exhaust ventilation or other engineering controls to keep airborne concentrations of vapors below their respective threshold limit value. Ensure that a working eyewash and safety shower are in the work area.

**Protective Equipment:** Wear splash goggles or safety glasses with side shields, synthetic apron, and neoprene or rubber gloves. In case of insufficient ventilation, wear an approved (NIOSH) respirator with organic vapor cartridge and dust/mist pre-filter.

**Exposure Guidelines / Other:**

Product Name	Exposure Limits
Acetone	OSHA PEL: TWA 1000 ppm ACGIH TLV: TWA 500 ppm    STEL 750 ppm
Cyclohexane	OSHA PEL: TWA 300 ppm ACGIH TLV: TWA 100 ppm
n-Hexane	OSHA PEL: TWA 500 ppm ACGIH TLV: TWA 50 ppm
Pentane	OSHA PEL: TWA 1000 ppm ACGIH TLV: TWA 600 ppm
Propane	OSHA PEL: TWA 1000 ppm ACGIH TLV: TWA 1000 ppm
Toluene	OSHA PEL: TWA 200 ppm    CL 300 ppm    500 ppm (10 minute max peak) ACGIH TLV: TWA 20 ppm

Consult local authorities and local regulations for exposure limits.

## 9 PHYSICAL AND CHEMICAL PROPERTIES

<b>Appearance:</b>	Liquid adhesive in pressurized container.	<b>Boiling Point:</b>	Not Available
<b>Physical State:</b>	Liquid	<b>Freezing / Melting point:</b>	Not Applicable
<b>Odor:</b>	Strong solvent	<b>Solubility:</b>	Not Soluble in Water
<b>pH:</b>	Not Applicable	<b>Specific Gravity / Density:</b>	Not Available
<b>Vapor Pressure:</b>	Not Available		
<b>Vapor Density:</b>	Greater than air		

## 10 STABILITY AND REACTIVITY

**Stability:** Product is stable as supplied.

**Conditions to Avoid:** All ignition sources and elevated temperatures.

**Materials to Avoid (incompatibility):** Copper and copper alloys, strong acids, alkalies, and oxidizers.

**Hazardous Decomposition Products:** Carbon Oxides (CO and CO<sub>2</sub>) and various Hydrocarbons.

**Hazardous Polymerization:** Will not polymerize.

## 11 TOXICOLOGICAL INFORMATION

<b>Acute Toxicity to Animals:</b>	Acetone:	Inhalation 4 hour LC50 = 30000 ppm (rat). Inhalation 4 hour LC50 = 18600 ppm (mouse). Oral LD50 = 5800 mg/kg (rat). Dermal LD50 > 16000 mg/kg (rabbit).
	Cyclohexane:	Oral LD50 = 12850 mg/kg (rat). Dermal LD50 > 18000 mg/kg (rabbit).
	Dimethyl Ether:	Inhalation 4 hour LC50 > 164000 ppm (rat). Inhalation 4 hour LC50 > 134350 ppm (mouse).
	n-Hexane:	Inhalation 4 hour LC50 = 38500 ppm (rat)

# MSDS **Material Safety Data Sheet**

Wilsonart International



MSDS Number: 01950  
Page 4 of 6

Wilsonart®/Lokweld® 700A Adhesive

Revision Date: 01/22/10  
Revision No: 4

Pentane: Oral LD50 = 28700 mg/kg (rat)  
Inhalation 4 hour LC50 > 6106 ppm (rat)  
Oral LD50 > 2000 mg/kg (rat)  
Propane: Inhalation 15 minute LC50 > 800000 ppm (rat).  
Toluene: Inhalation 4 hour LC50 = 7585 ppm (rat)  
Inhalation 4 hour LC50 = 7100 ppm (mouse)  
Oral LD50 = 5580 mg/kg (male rat)  
Dermal LD50 = 12125 mg/kg (rabbit)

**Chronic Toxicity to Animals:** No additional information.  
**Acute Toxicity to Humans:** No additional information.  
**Chronic Effects on Humans:** No additional information.  
**Carcinogenic Effects:** No additional information.  
**Mutagenic Effects:** No additional information.  
**Teratogenic Effects:** Classified PROVEN for human (Toluene).  
**Developmental Toxicity:** Classified PROVEN for human (Toluene).

## 12 ECOLOGICAL INFORMATION

**Ecotoxicity:** Product may kill grasses and small plants. Non-toxic to fish. Moderately toxic to amphibians by preventing dermal respiration. May cause gastrointestinal distress to birds and mammals by ingestion.  
**BOD5 and COD:** Not Available.  
**Biodegradable / OECD:** Not Available.  
**Toxicity of the Products of Biodegradation:** Not Available.  
**Special Remarks on the Products of Biodegradation:** Not Available.

## 13 DISPOSAL CONSIDERATIONS

Spilled, contaminated, or waste material should be put into a suitable container and handled according to Federal, State, and local regulations. Contact a qualified waste management company for assistance.  
Contents are under pressure. Do not puncture or incinerate container.  
Dispose of in accordance with Federal, State, and local regulations.

## 14 TRANSPORT INFORMATION

**DOT Classification:** ORM-D  
**Proper Shipping Name:** Consumer Commodity  
**Hazard Class:** 2.1  
**Packing Instructions:** 173.306  
**Marine Pollutant:** No.

## 15 REGULATORY INFORMATION

### U.S. Federal Regulations

Chemical (& CAS Number)	SARA 302 (EHS)TPQ	SARA 304 (EHS)Rq	SARA 313 <i>de minimis</i>	CERCLA Rq	CAA 112(r) TQ	RCRA Code
Acetone (67-64-1)				5000		U002
Cyclohexane (110-82-7)			1	1000		U056
Dimethyl Ether (115-10-6)					10000	
n-Hexane (110-54-3)			1	5000		
Pentane (109-66-0)					10000	
Propane (74-98-6)					10000	
Toluene (108-88-3)			1	1000		U220

All quantities in pounds

## State Regulations

Chemical (& CAS Number)	CA Prop 65	MA RTK	MN RTK	NJ RTK	PA RTK	RI RTK
Acetone (67-64-1)		X	X	X	X	X
Cyclohexane (110-82-7)		X	X	X	X	X
Dimethyl Ether ( 115-10-6)		X	X	X	X	X
n-Hexane (110-54-3)		X	X	X	X	X
Pentane (109-66-0)		X	X	X	X	X
Propane (74-98-6)		X	X	X	X	X
Toluene (108-88-3)	X	X	X	X	X	X

## International Regulations

**DSL (Canada):** The chemicals in this product are listed.

**EINECS:** The chemicals in this product are listed.

**WHIMS:** A, B1, & D2B.

## 16 OTHER INFORMATION

### References

Lewis, R. J., *Rapid Guide to Hazardous Chemicals in the Workplace*, 4<sup>th</sup> ed., Wiley-Interscience, New York, 2000.

*NIOSH Pocket Guide to Chemical Hazards*, Department of Health and Human Services, National Institute for Occupational Safety and Health, 2004.

*Patty's Toxicology*, 5<sup>th</sup> ed. John Wiley & Sons, Inc. 2001.

*TLVs and BEIs, Threshold Limit Values for Chemical Substances and Physical Agents & Biological Exposure Agents*, ACGIH Worldwide, Cincinnati, 2007.

### Glossary

ACGIH – American Conference of Governmental Industrial Hygienists

ASTM – American Society for Testing and Materials

ADR – Agreement on Dangerous Goods by Road (Europe)

BOD5 – Biological Oxygen Demand in 5 days

CAA – Clean Air Act

CAS – Chemical Abstracts Services

CEPA – Canadian Environmental Protection Act

CERCLA – Comprehensive Environmental Response, Compensations, and Liability Act

CFR – Code of Federal Regulations

CL – Ceiling

CWA – Clean Water Act

DOT – Department of Transportation

DSCL – Dangerous Substances Classification and Labeling (Europe)

DSL – Domestic Substance List (Canada)

EEC/EU – European Economic Community/European Union

EINECS – European Inventory of Existing Commercial Chemical Substances

HCS – Hazard Communication System

HMIS – Hazardous Material Information System

IARC – International Agency for Research on Cancer

LD50/LC50 – Lethal Dose/Concentration kill 50%

LDLo/LCLo – Lowest Published Lethal Dose/Concentration

NFPA – National Fire Prevention Association

NIOSH – National Institute for Occupational Safety & Health

NTP – National Toxicology Program

OSHA – Occupational Safety & Health Administration

# **MSDS** *Material Safety Data Sheet*

**Wilsonart International**



MSDS Number: 01950  
Page 6 of 6

**Wilsonart®/Lokweld® 700A Adhesive**

Revision Date: 01/22/10  
Revision No: 4

**PEL – Permissible Exposure Limit**  
**RCRA – Resource Conservation and Recovery Act**  
**SARA – Superfund Amendments and Reorganization Act**  
**STEL – Short Term Exposure Limit (15 minutes)**  
**TDG – Transportation of Dangerous Goods (Canada)**  
**TLV-TWA – Threshold Limit Value-Time Weighted Average**  
**TSCA – Toxic Substances Control Act**  
**WHMIS – Workplace Hazardous Material Information System**

**CHEMTREC:**  
**800-424-9300 (USA)**  
**703-527-3887 (International)**

**Notice to Reader**

*To the best of our knowledge, the information contained herein is accurate. However, neither the above named manufacturer nor any of its subsidiaries assumes any liability whatsoever for accuracy or completeness of the information contained herein.*

*Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.*

---

**END OF MSDS DOCUMENT**